

Pave-Guard Anti Slip Acrylic Coating

Pave-Guard Anti Slip Acrylic is a water thinned, lead free self cross-linking acrylic paving paint designed to give excellent adhesion and a durable anti slip surface.

About The Product

Anti slip coating to AS4586-2004 rating 'V' wet slip test.

Surfaces:

- Pavements
- Concrete Floors
- Asphalt surfaces
- Brickwork
- Timber
- Steel / Aluminium

Colour: Neutral base tint able to a wide range of colours as per AS2700 industrial colour range.

Gloss: low sheen

Toxicity : Lead free, non toxic when dry.

Drying Time: Touch dry in 30 minutes. Recoat in 2 hours. Drying and recoat will be longer in cold or damp conditions.

Flammability: Non flammable

Coverage: Approximately 2 – 5 m² per litre, depending on the surface profile and application technique.

Thinning: In hot conditions thin with up to 50 mls of water per litre if necessary.

.Apply By: Brush, Roller (10-12 napp) Texture Spray system (Graco) Conventional or airless spray gun (32 thou tip)

Previously Painted Surfaces Bitumen, Concrete

- Remove all dirt, grease and loose or flaking material
- Treat affected surfaces to remove mould, efflorescence or other defects.
- Fill holes voids and cracks with Transpac PatchPak cement repair
- Apply two coats Pave-Guard Anti Slip Acrylic coating.

New Surfaces

- Surface must be dry and free of dust and other contaminants.

Timber, Concrete & Brick

- Apply Timberguard Primer

Steel & Aluminium

- Apply Maxi Metal Primer

Asphalt

- Wait minimum 60 days – No primer

Finish Coat all Surfaces

- Apply 2 coats Pave-Guard Anti Slip Acrylic coating.

Application

Stir thoroughly using a broad flat paddle in a scooping motion. Do not apply if temperature is below 10C or likely to fall below 10C during drying or if rain is imminent. Refer to web site for full details: www.ultravgroup.com.au

Additional:

Can be seal coated with **Pave-Guard Clear** water based acrylic finish sealer 2 - 4 hours after application of Pave-Guard for added protection from moisture, solvents and oils. Refer to Data sheet **Pave-Guard Clear**

Clean Up: Tap water

Safety and Environment

- Keep out of the reach of children
- Ensure adequate ventilation during use and drying
- Refer Material Safety Data Sheet for full information
- Do not pour paint products down sewers or stormwater drains
- Dispose of unused paint and containers through special collection services
- Contact your local council for information about disposal

First Aid

If swallowed :

- Do not induce vomiting
- Drink plenty of water
- Seek medical advice

If in eyes:

- Flood eyes with water for 15 minutes.
- If irritation persists seek medical attention.

To obtain a Material Safety Data Sheet contact:-

Ultra V Group Customer Service

Tel: 03 98748913

Fax: 03 98748914

Disclaimer: The information in this data sheet is believed to be as up to date as possible. No responsibility is accepted or warranty given or implied since the application procedures are outside the control of the company.

